

4-IN-1 POWERFACTOR™ DIMMABLE DRIVER

The ultimate stocking driver. Does it all:

- MLV dimming
- ELV dimming
- 0-10V dimming
- 1-10V dimming
- 120-277V AC input
- Wet location
- Integrated junction box



120-277V AC Input
MLV/ELV dimmer
connection for
those using MLV or
ELV Dimmers

0-10V/1-10V Option
Connection for
those using 0-10V
or 1-10V dimmers

Output
Connection to low-
voltage tape light.
Models available up
to 384 Watts!

ALLOYLED®

Item #	Output Voltage	Wattage	Wet Location	Dimensions (L x W x H)	Class 2
AL-98-10-12030-4in1	12V DC	30W	Y	6.50 x 3.72 x 1.57 in.	Y
AL-98-10-12060-4in1	12V DC	60W	Y	7.40 x 3.72 x 1.57 in.	Y
AL-98-10-12120-4in1	12V DC	120W	Y	8.66 x 3.72 x 1.57 in.	N
AL-98-10-24030-4in1	24V DC	30W	Y	6.50 x 3.72 x 1.57 in.	Y
AL-98-10-24060-4in1	24V DC	60W	Y	7.40 x 3.72 x 1.57 in.	Y
AL-98-10-24096-4in1	24V DC	96W	Y	8.66 x 3.72 x 1.57 in.	Y
AL-98-10-24150-4in1	24V DC	150W	Y	10.24 x 4.13 x 1.77 in.	N
AL-98-10-24200-4in1	24V DC	200W	Y	10.24 x 4.13 x 1.77 in.	N
AL-98-10-24300-4in1	24V DC	300W	Y	10.94 x 4.33 x 1.77 in.	N
AL-98-10-24384-4in1-MT	24V DC	4*96W	Y	12.80 x 5.51 x 1.89 in.	Y