

## STANDARD QUOTE

Components to be cut and assembled in-field

**\*PLEASE FILL OUT COMPLETELY\***

For a prioritized quote, please fill out all required information.

Job Name: \_\_\_\_\_

Job Location / Address: \_\_\_\_\_

If incompatible products are listed below, allow Alloy to substitute products to ensure all components are compatible.

Individual Run Lengths \_\_\_\_\_  
(specify exact lengths,  
e.g. 12'5" or 149 in.)  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Power Supply

plug-in

hard-wired

dimmable

non-dimmable

Are Class 2 power supplies required?

(No circuit greater than 60W for 12V system,  
no circuit greater than 96W for 24V system.)

no  yes

Kelvin Temp. (CCT) \_\_\_\_\_ 3000K (default)

Location  dry  wet

Tape Light  
Output (per ft.)

White Light (keep in mind not all lights have wet location option)

3W /  
129-247lm  
(default)

1.5W /  
87-121lm

2.7W /  
160-224lm

4.4W /  
294-379lm

Varien 5.5  
315-348lm

5.5W /  
457-477lm

6.6W /  
631-835lm

8W /  
810-1106lm

Neon 100 SB

Neon 200 TB

Color Changing (keep in mind not all lights have wet location option)

RGB  
2.2W

RGB  
4.4W

RGB-W  
4.4W

RGB-W  
4.7W

RGB-W  
5.9W

RGB-W  
8.8W

Channel and Cover  no  yes (specify style or location) \_\_\_\_\_

If yes, is a hotspot-free solution required?  no  yes

**ADDITIONAL DETAILS YOU CAN SUPPLY WILL EXPEDITE THE QUOTING PROCESS**

---

---

---

---

Dealer Name: \_\_\_\_\_

Alloy LED, LLC  
6121 Vallejo St.  
Emeryville, CA  
94608

CALL: 800.910.LEDS (5337)  
FAX: 510.338.6173  
Email: solutions@alloyled.com

